



Humidification and Evaporative Cooling Systems

## GoFog™ Water Treatment Selection

GoFog™ Water Treatment Systems have the option of coming fully assembled on a powder coated carbon steel frame or as loose equipment that can be installed in the field. Additional capacities are available upon request.

GoFog™ Reverse Osmosis System						
Model	MRO-2500	MRO-5400	MRO-7200	MRO-10800	MRO-14400	MRO-22000
<b>Maximum Output (GAL/DAY)</b>	2,500	5,400	7,200	10,800	14,400	22,000
<b>Maximum Output (LBS/HR)</b>	850	1,875	2,500	3,750	5,000	7,500
<b>Maximum Output (GPM)</b>	1.7	3.75	5.0	7.5	10.0	15.0
<b>Pre-treatment</b>	5 micron pre-filter, carbon filter, water softener					
<b>Post-treatment</b>	UV sterilization, storage tank, recirc pump, transfer pump, bladder tank					
<b>Storage Tank (GAL)</b>	160	300	425	500	1000	1500
<b>Bladder Tank (GAL)</b>	40	40	40	80	80	80
<b>Assembly Options</b>	Skid mounted factory assembly or field assembly loose components					

Product will vary based on feed water temp and quality. Output based on 77F water temp and 500 ppm TDS.

Please ask your GoFog representative for a proper selection based on your specific water quality.