



Humidification and Evaporative Cooling

| GoFog™ Pump Units | | | | |
|--|--|-----------------|-----------------|-----------------|
| Model | GFP-800 | GFP-1750 | GFP-3600 | GFP-6000 |
| Maximum Fog Output (LBS/HR) | 800 | 1,750 | 3,600 | 6,000 |
| Maximum Pump Flow (GPM) | 1.6 | 3.5 | 7.2 | 12.0 |
| Operating Pressure (PSI/BAR) | 1,000 / 69 | | | |
| CAT Pump Model | 3CP1231 | 5CP6251 | 7CP6111 | 2511 |
| Direct Drive / Belt Drive | Direct | Direct | Direct | Belt |
| Maximum Pump Speed (RPM) | 1,200 | 1,200 | 1,200 | 870 |
| Pump Motor (HP) | 3.0 | 5.0 | 10.0 | 15.0 |
| ABB VFD (HP) | 3.0 | 5.0 | 10.0 | 15.0 |
| Full Load Amps (460V) | 8.0 | 15.0 | 20.0 | 29 |
| Weight (LBS) | 450 | 550 | 650 | 750 |
| Inlet Water Connection | 3/4" FNPT | 3/4" FNPT | 1" FNPT | 1" FNPT |
| Pump Cooling | Bypass to RO storage tank or finned-tube heat exchangers | | | |
| Controller | Horner XL4 OCS with 3.5" Color Touchscreen | | | |
| Communication | Modbus, BACnet, LON, and others available. Please specify the required BMS protocol. | | | |
| | | | | |
| Dimensions (LxDxH) - Single Pump | 34" x 27" x 65" | 34" x 27" x 65" | 40" x 29" x 65" | 48" x 30" x 65" |
| Dimensions (LxDxH) - Dual Pump | 34" x 30" x 65" | 34" x 30" x 65" | 40" x 30" x 65" | 60" x 60" x 66" |
| * Additional pump rack sizes are available. Please ask your GoFog™ representative for further information. | | | | |

About GoFog, Inc.

Headquartered just outside of Charlotte NC, GoFog provides custom built atomizing humidifiers for the commercial, industrial, and agricultural markets.